



RI ST30
ALL STEEL
RADIAL TYRES

Tyre Info						Rim	Technical Information								Inflated Unloaded Dimensions	
Product Code	Tyre Size	Star Rating	TT/ TL	LI / SI	TRA Code	Rec. Rim (inch)	Speed (km/h)	Inflation Pressure (Bar / psi)	Load Capacity (kg)						Overall Diameter (mm)	Section Width (mm)
									3.5 Bar / 51 Psi	3.75 Bar / 54 psi	4.0 Bar / 58 psi	5.0 Bar / 73 Psi	5.25 Bar / 76 psi	5.75 Bar / 83 Psi	6.50 Bar / 94 psi	
*URC025205702GTK	20.5 R25	**	TL	193 A2 / 177 B	L3 / E3	17.00/2.0	10 km / h	-	-	8000	9500	9750	10300	11500	1492	520
							50 km / h	5300	5600	5800	6900	7300	-	-		
*URC025235702GTK	23.5 R25	**	TL	201 A2 / 185 B	L3 / E3	19.50/2.5	10 km / h	-	-	10300	12150	12500	13200	14500	1617	597
							50 km / h	6700	7100	7500	9000	9250	-	-		
*URC025265702GTK	26.5 R25	**	TL	209 A2 / 193 B	L3 / E3	22.00/3.0	10 km / h	-	-	12850	15000	15500	16500	18500	1750	673
							50 km / h	8500	9000	9500	11200	11500	-	-		